

**PCT**WORLD INTELLECTUAL PR  
Internations

INTERNATIONAL APPLICATION PUBLISHED UNDER

(51) International Patent Classification <sup>6</sup> :**B01D 65/02, 61/20, 61/22, 63/02, 65/08,  
61/18, 65/00****A1**

(11)

**WO 9607470A1**


(43) International Publication Date:

**14 March 1996 (14.03.96)**(21) International Application Number: **PCT/AU95/00587**(22) International Filing Date: **8 September 1995 (08.09.95)**

(30) Priority Data:

**PM 8006****9 September 1994 (09.09.94)****AU**(71) Applicant (for all designated States except US): **MEMTEC LIMITED [AU/AU]; 1 Memtec Parkway, South Windsor, NSW 2756 (AU).**

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BECK, Thomas, William [AU/AU]; 31 Drummond Street, South Windsor, NSW 2756 (AU). DRUMMOND, Humphrey, John, Jardine [AU/AU]; 33 Drummond Street, South Windsor, NSW 2756 (AU). LEE, Matthew, Brian [AU/AU]; RMB 911 Townsview, Pyalong Road, Lancefield, VIC 3435 (AU). KOPP, Clint, Virgil [US/AU]; 53 Tuckwell Road, Castle Hill, NSW 2154 (AU). JOHNSON, Warren, Thomas [AU/AU]; 8 Scarborough Crescent, Bligh Park, NSW 2756 (AU).**(74) Agent: **SHELSTON WATERS; 60 Margaret Street, Sydney, NSW 2000 (AU).**(81) Designated States: **AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).****Published***With international search report.*(54) Title: **CLEANING OF HOLLOW FIBRE MEMBRANES**

(57) Abstract

A method and apparatus for recovering fine solids from a liquid feed suspension is disclosed. The apparatus has an operating cycle including a concentration part of the cycle in which solids present in the feed suspension are concentrated and a backwash part of the cycle in which supply of feed suspension to the concentrator is interrupted, the concentrator comprises a shell (11), and a plurality of elastic, hollow, microporous, polymer fibres (12) being fixed at their ends within the shell (11). Pressurized feed suspension is supplied to the outside of the fibres during said concentration part of the cycle and the filtrate may be withdrawn from the fibre lumens during the operating cycle. During the backwash cycle the concentration part of the cycle is terminated by ceasing supply of feed to said exterior surface of the fibres (12). The shell (11) is then sealed and the remaining filtrate removed from the lumens. A source of fluid under pressure is then applied to said lumens before, at the same time as, or just after opening the shell (11) to atmosphere, to cause explosive decompression through the walls of the fibres (12) whereby the fluid under pressure passes through said walls. The pressure level in said lumens is maintained at a predetermined value for a sufficient time following said decompression to cause substantial portions of solids lodged within and/or on the fibre walls to be dislodged. The dislodged contaminant matter is then washed away by the application of a flow of liquid over the surface of the fibre walls; and the concentration part of the operating cycle is recommenced by introducing the supply of feed suspension to said exterior surface of said fibres (12).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

5

**TITLE: CLEANING OF HOLLOW FIBRE MEMBRANES**10 **TECHNICAL FIELD**

The present invention relates to concentration of solids in a suspension using a hollow fibre membrane and, in particular forms, to methods and apparatus for periodically cleaning by backwashing the hollow fibre membranes.

**BACKGROUND ART**

15 Prior art methods of concentrating solids in a liquid suspension are described in Australian patent specifications 576,424 and 582,968. The text and drawings of these specifications are incorporated herein by cross-reference. In that prior art, concentration is effected by a filter element that comprises a bundle of hollow, porous, polymeric fibres in a closed cartridge or shell. Polyurethane potting compound is used to hold the  
20 respective ends of the fibres in place within the cartridge without blocking the fibre lumens and to close off each end of the cartridge.

- 2 -

The transmembrane pressure differential necessary to effect concentration of the solids in the prior art is achieved by pressurising the feedstock which necessitates the use of pumps, other ancillary equipment and, of course, a closed filter cartridge.

Backwashing of such prior art concentrators involves increasing the pressure on  
5 both sides of the hollow fibres within the closed shell to a relatively high value before suddenly releasing that pressure on the shell side of the fibre walls to effect a sudden pressure differential across the walls which causes a backwash action.

#### DISCLOSURE OF INVENTION

It is an object of this invention to provide an improved method of using a  
10 reverse-flow mode to dislodge solids retained by filter elements to ensure rapid removal of those retained solids and in which the separation and dislodgement modes may be repeated for prolonged periods of time.

The present invention, in at least some embodiments, provides a method of  
backwashing a hollow fibre filter which retains some of the features of the prior art, but  
15 optimizes a number of these features to provide improved performance.

Accordingly, in one broad form of the invention, there is provided a method of  
backwashing a plurality of hollow fibres having microporous walls which have been  
subjected to a filtration operation wherein feed containing contaminant matter is applied  
to the exterior surface of said hollow fibres and filtrate withdrawn from the ends of the  
20 lumens of the fibres, the fibres being contained within a shell or housing, said method comprising:

- (a) terminating the filtration operation by ceasing supply of feed to said exterior surface of said fibres,

- 3 -

(b) sealing the shell and substantially removing remaining filtrate from said lumens,

(c) applying a source of fluid under pressure to said lumens before, at the same time as, or just after opening the shell to atmosphere, to cause explosive

5 decompression through the walls of the fibres whereby said fluid under pressure passes through said walls;

(d) maintaining the pressure level in said lumens at a predetermined value for a sufficient time following said decompression to cause substantial portions of contaminant matter lodged within and/or on said fibre walls to be dislodged;

10 (e) washing dislodged contaminant matter away by the application of a flow of liquid over the surface of said fibre walls; and

(f) recommencing the filtration operation by introducing said supply of feed to said exterior surface of said fibres.

For preference, during the backwash phase, the time lapse between the start of an  
15 increase in negative transmembrane pressure (TMP) and such TMP reaching a maximum value corresponding to the explosive decompression, is in the range of about 0.05 seconds to about 5 seconds.

Preferably, the fibres are rewetted prior to recommencing the filtration operation.

Preferably, feed liquid is pumped into the shell side of the filter while fluid  
20 pressure is still being applied to said lumens. This results in liquid/fluid turbulence or frothing around the membrane pores causing further improved dislodgement of retained solids. The fluid pressure during this phase preferably should exceed the shell side pressure by about 10kPa to about 800kPa.

- 4 -

Preferably, the steps of the method are carried out as a continuous process utilizing repetitive cycles of solids retention and backwash.

As an alternative preferred form, step (b) is effected by allowing said remaining filtrate to drain out of said lumens of its own volition.

5       According to a further broad aspect, the present invention provides a concentrator for recovering fine solids from a liquid feed suspension and having an operating cycle including a concentration part of the cycle in which solids present in the feed suspension are concentrated and a backwash part of the cycle in which supply of feed suspension to the concentrator is interrupted, said concentrator comprising:

- 10       (i)     a shell;
- (ii)    a plurality of elastic, hollow, microporous, polymer fibres being fixed at their ends within the shell;
- (iii)   means for supplying pressurized feed suspension to the outside of the fibres during said concentration part of the cycle;
- 15       (iv)    means for withdrawing filtrate from the fibre lumens during said operating cycle;
- (v)     means for terminating the concentration part of the cycle by ceasing supply of feed to said exterior surface of said fibres;
- (vi)    means for sealing and opening the shell to atmosphere;
- 20       (vii)   means for substantially removing remaining filtrate from said lumens;
- (viii)  means for applying a source of fluid under pressure to said lumens before, at the same time as, or just after opening the shell to atmosphere, to cause explosive

- 5 -

decompression through the walls of the fibres whereby said fluid under pressure passes through said walls;

- (ix) means for maintaining the pressure level in said lumens at a predetermined value for a sufficient time following said decompression to cause
- 5 substantial portions of solids lodged within and/or on said fibre walls to be dislodged;
- (x) means for recommencing the concentration part of the operating cycle by introducing said supply of feed suspension to said exterior surface of said fibres.

Preferably, the concentrator includes means for rewetting the fibres before recommencing concentration.

- 10 Where fluid pressure is applied to remove the filtrate from the lumens, this pressure is typically in the range of about 10 to about 600 kPa. The fluid pressure applied to the lumens prior to the decompression is typically in the range of about 100 to about 1200 kPa.

- The penetration of gas into the pores of a membrane is resisted by the surface
- 15 tension forces of the contained wall-wetting liquid according to well known theory. Indeed, surface tension is conveniently measured by the breakthrough pressure needed to force a bubble out of a submerged orifice. For common systems (such as oil in hydrophobic pores or water in hydrophilic pores) the breakthrough pressures are much higher than the usual operating pressures of the filter.

- 20 Prior art hollow-fibre type ultrafilters are usually fed from the inside of the fibres for many well known reasons. However, according to the present invention, feedstock is applied to the outside of the fibres and gas is introduced into the lumen of the fibre as the back-wash medium. In some cases, the lumen pressure swells a suitably designed fibre

- 6 -

so that the pores are enlarged whereby the particles are freed and swept away in the expansion of the back-wash gas.

In some cases, especially where very fine-pored interstitial material is deposited in relatively coarse-pored base fibre, it is advantageous to back-wash first with a small amount of permeate already in the membrane lumen and follow with the high pressure gas back-wash. In this way, the small amount of permeate adequately washes out fine blocking material from within the interstices, and the overall cleaning is completed by the higher pressure gas swelling the base pores and erupting around elastic openings. The pores must close again rapidly to reseal the holes and the base material must not crack by work hardening and must remain within its modified elastic limit.

Preferably, the fibres are made from thermoplastic polymers such as:

poly(propylene), poly(4-methylpent-1-ene), co-polymers of polypropylene, poly(vinylidenedifluoride), poly(sulphones), poly(phenylene sulphides), poly(phenylene oxides), phenoxy resins, polyethylene, poly(tetrafluoroethylene) and poly(chlorotrifluoroethylene).

The use of gas as a back-wash medium enables the removal of fouling species by explosive decompression of the gas through the membrane structure for the minor part and at the outer membrane surface for the major part. Thus, the gaseous back-wash step is carried out at a pressure which is sufficient to overcome the effect of the surface tension of the continuous phase of the feedstock within the pores of the membrane.

Hitherto, it was felt the gas backwashing phase should be limited to below 5 seconds to avoid drying out of the fibres and thus difficulty in recommencing filtration due to gas bubble retention in the fibre pores. The introduction of improved rewetting



- 7 -

techniques has overcome this problem and it has been discovered that extending the gas backwash phase beyond 5 seconds has significant advantages. Time periods of up to 60 seconds have been found to be effective. A longer backwash provides improved removal of trapped solids. Also, where liquid is reintroduced to the shell prior to completion of the gas backwash, it has enabled the overlap where gas and liquid are both present to be extended. An overlap time of about 1 to about 30 seconds is preferable. This is desirable in large arrays where it may take considerable time, with normal pump pressures, to refill the shells with liquid. The extended time period enables normal pumps to be used to achieve the above overlap while it also avoids maldistribution of pressure within large filter arrays by allowing relatively slow refilling of the filter shells.

In another form of the invention, the high pressure fluid application to the lumens may be pulsed to provide a number of explosive decompressions within the backwashing phase. These individual pulses are preferably between about 0.1 seconds and about 5 seconds in duration. This provides an advantage of reducing gas consumption in the backwash phase. The pulsing may be achieved by sealing and opening the shell at appropriate time intervals sufficient to allow pressure within the lumens to build up to a required level. Alternatively, the pressure supply may be pulsed to achieve the same effect. In a further embodiment, the pressure may be varied between a high and low level without actual total shut off of pressure.

## 20 BRIEF DESCRIPTION OF DRAWINGS

Preferred embodiments of the present invention will now be described, by way of example only, with reference to the following examples and accompanying drawings, in which:

- 8 -

Figure 1 shows a schematic representation of a hollow fibre cross-flow concentrator to which the present invention is applicable in an operating mode;

Figure 2 shows the concentrator of Figure 1 in backwash mode;

Figure 3 shows a graph of transmembrane pressure (TMP) versus time for a  
5 standard backwash;

Figure 4 shows a similar graph to Figure 3 using a backwash according to one aspect of the invention;

Figure 5 shows a normalized flow/TMP versus time graph for a standard backwash;

10 Figure 6 shows a normalized flow/TMP versus time graph for the same type of machine as Figure 5 but using the backwash according to one aspect of the invention;

Figure 7 shows a graph of TMP versus time for a backwash where feed liquid is pumped into the filter while the gas backwash is still applied;

Figure 8 shows a normalized flow/TMP versus time graph for a standard  
15 backwash;

Figure 9 shows a normalized flow/TMP versus time graph for the same type of machine as Figure 8 but introducing feed liquid during the backwash cycle;

Figure 10 shows a normalized flow/TMP versus time graph for a standard backwash at a further installation; and

20 Figure 11 shows a normalized flow/TMP versus time graph for the same type of machine as Figure 10 but introducing feed liquid during the backwash cycle.

### MODES FOR CARRYING OUT THE INVENTION

The hollow fibre cross-flow concentrator 10 shown in Figs. 1 and 2 includes a cartridge shell 11 within which is positioned a bundle of hollow, porous, polymeric fibres 12. In this instance, each fibre is made of polypropylene, has an average pore size of 0.2 $\mu$ m, an internal lumen diameter in the range 250 $\mu$ m to 310 $\mu$ m and a fibre diameter in the range 500 $\mu$ m to 650 $\mu$ m. There may be between 2,800 to 30,000 hollow fibres in the bundle 12 but this number as well as the individual fibre dimensions may be varied according to operational requirements.

Polyurethane potting compound 13,14 holds the ends of the fibres 12 in place without blocking their lumens and closes off each end of the shell 11. The liquid feed suspension to be concentrated is pumped into the shell 11 through feed suspension inlet 15 and passes over the external walls of the hollow fibres 12. Some of the feed suspension passes through the walls of the fibres 12 into the lumens of the fibres to be drawn off through the lumen outlet port 16 as clarified liquid.

The remaining feed suspension and some of the rejected species flows between the fibres 12 and leaves the shell 11 through outlet 17. The remainder of the rejected species is held onto or within the fibres or is otherwise retained within the shell. Lumen inlet port 18 remains closed during the operating mode of the concentrator shown in Fig. 1.

In order to remove the retained species, lumen outlet port 16 is closed so that the flow of clarified liquid is stopped. The clarified liquid is then removed from the lumens by natural drainage or by introducing a pressurized gas through lumen inlet port 18 to force the liquid from the lumens. Upon completion of the removal of the filtrate liquid,

- 10 -

high pressure compressed gas is introduced through inlet 18 and the lumens of the fibres  
12. The liquid-filled shell is sealed and gas cannot penetrate the porous walls even  
though the gas pressure is now raised well above the normal bubble point of the fibre  
walls because the liquid within the shell is relatively incompressible. A reservoir of high  
5 pressure gas is thus accumulated in the fibre lumens.

The shell outlet 17 is then opened which allows gas to penetrate the pores along  
the whole length of each fibre. This results in a explosive decompression of the  
pressurized gas through the walls of the fibres resulting in the retained solids in the fibre  
walls being dislodged from the fibres into the feed side of the filter. The initial  
10 breakthrough of gas through the fibre wall results in a tendency for pressure to drop in  
the lumens. It is desirable if this pressure can be maintained for a short period following  
decompression to cause increased flow through the fibre wall and greater removal of  
retained solids. This is preferably achieved by providing a large diameter pressure feed  
to the lumens and/or a higher pressure to compensate for pressure drop. In some cases, it  
15 is desirable to admit gas through both lumen ports 16 and 18 after carrying out the above  
described pressurised, trapped gas operation.

In alternate embodiments, the shell is opened just before or at the same time as  
the pressurized gas is applied to the lumens.

Referring to the accompanying graphs, a number of examples will now be  
20 described to illustrate the improved performances provided by embodiments of the  
invention.

- 11 -

**EXAMPLE 1**

An M10C (250 $\mu$ m lumen) filter unit was run using a larger airline to provide an increased and prolonged pressure to the lumens following the explosive decompression phase. A 2.5cm airline was used instead of a standard 10mm airline. There was no  
5 pressurize stage used during this improved backwash and the negative transmembrane pressure (TMP) obtained on the filter unit was 620kPa compared with 380kPa for a standard backwash. The air consumption was higher than that for a standard backwash. The pressure profiles of the two different backwashes are shown in Figures 3 and 4.

During the standard backwash shown in Figure 3, it can be seen that a time of  
10 0.65 seconds elapses between the start of the explosive decompression phase and the point at which maximum TMP is obtained. Analysis of the similar section of the improved backwash shows the time to reach maximum negative TMP was only 0.15 seconds. The reaching of maximum TMP corresponds with the air breaking through the walls of the fibre and expelling the fluid within the wall pores. The period between the  
15 opening of the shell and the breakthrough is a liquid backwash phase as the liquid within the pores is being moved outwardly from the lumen toward the shell side. When the air breaks through the fibre wall the liquid backwash phase is completed. Preferably this period is within the range 0.05 seconds to 5 seconds.

The results of consecutive runs on the test filter unit comparing the standard and  
20 the improved backwash (termed a "mega" backwash herein) procedures are shown in attached TABLE 1.

As can be seen from TABLE 1 and the performance graphs (Figures 5 and 6), the TMP rise is significantly reduced when the 'mega' backwash is used. The TMP rise per

- 12 -

day for the 'mega' backwash was approximately one quarter of the TMP rise seen with the standard backwash. This result means that machines could be run for longer between cleaning cycles, or the machines could give a higher throughput for the same cleaning interval.

5 **EXAMPLE 2**

This example relates to the procedure where feed liquid is reintroduced to shell while the gas backwash is still proceeding. A trial was carried out on surface water to compare a standard backwash with a backwash stage using pressurized gas plus feed liquid. This stage is typically referred to as an "air on pump on" stage (AOPO stage).

10 Two identical 1M10C filter units were set up to run side by side on river water. One machine used a standard pressurize backwash cycle, whilst the other incorporated an extra stage. The extra stage consisted of switching on the feed pump whilst still applying high pressure air through the hollow fibre walls. The resultant two phase flow across the fibre bundle appeared to be very effective in removing fouling from the  
15 membrane module.

The two filter units were running at a constant flow of 200 L/hr/em, using a pump with a variable speed drive to keep the set flow. The area unit em is related to the surface area of an original Memtec filter module. Figures 8 and 10 illustrate the results of two consecutive runs of a filter unit and show that the TMP, when the standard  
20 backwash was used, rose to 400kPa within 4 days of operation. At this point the unit could no longer maintain the set flow of 200 L/hr/em. Figures 9 and 11 show that when the AOPO stage was used the TMP remained below 150kPa for 7 days. The result of this is that the filter units could maintain a higher flow rate for a longer period of time

- 13 -

when the AOPO stage is used in the backwash. This is important to filter unit efficiency as the units require chemical cleaning when the TMP reaches a predetermined value.

Typically during the backwash the decompression stage consists of the lumens being pressurized to 600kPa, then the shell side valves being released whilst still  
5 supplying air to the lumens (for typically 1 to 3 seconds on most applications). The AOPO stage would extend the amount of time air is resupplied to the fibre lumens by typically an extra 1 to 30 seconds on M10 units.

It will be appreciated that further embodiments and exemplifications of the invention are possible without departing from the spirit or scope of the invention  
10 described.

- 14 -

**M10C (250 µm lumens) comparison of 'mega' and standard backwashes**

<i>BACKWASH TYPE</i>	<i>STANDARD</i>	<i>MEGA</i>
Module Type	PP M10C (20,000 fibres)	PP M10C (20,000 fibres)
Feed Type	River water	River water
Feed Turbidity (NTU)	8	7
Feed Temperature (°C)	9.3	9.3
TMP (kPa)	103	92
TMP Range (kPa)	82 to 108	86 to 91
Instantaneous Flow* (L/hr/module)	2084	2223
Instantaneous Flow* (L/hr/module) at 20°C	2855	3045

5 \*Instantaneous flow is the average of instantaneous flowrates measured.

**Table 1**



- 15 -

**CLAIMS:-**

1. A method of backwashing a plurality of hollow fibres having microporous walls which have been subjected to a filtration operation wherein feed containing contaminant matter is applied to the exterior surface of said hollow fibres and filtrate withdrawn from  
5 the ends of the lumens of the fibres, the fibres being contained within a shell or housing, said method comprising:

(a) terminating the filtration operation by ceasing supply of feed to said exterior surface of said fibres,

(b) sealing the shell and substantially removing remaining filtrate from said  
10 lumens,

(c) applying a source of fluid under pressure to said lumens before, at the same time as, or just after opening the shell to atmosphere, to cause explosive decompression through the walls of the fibres whereby said fluid under pressure passes through said walls;

15 (d) maintaining the pressure level in said lumens at a predetermined value for a sufficient time following said decompression to cause substantial portions of contaminant matter lodged within and/or on said fibre walls to be dislodged;

(e) washing dislodged contaminant matter away by the application of a flow of liquid over the surface of said fibre walls; and

20 (f) recommencing the filtration operation by introducing said supply of feed to said exterior surface of said fibres.

2. A method of backwashing according to claim 1 wherein during step (c), the time lapse between the start of an increase in negative transmembrane pressure (TMP) and

- 16 -

such TMP reaching a maximum value corresponding to the explosive decompression, is in the range of about 0.05 seconds to about 5 seconds.

3. A method of backwashing according to claim 1 or claim 2 wherein the fibres are rewetted prior to recommencing the filtration operation.
- 5 4. A method of backwashing according to any one of claims 1 to 3 wherein feed liquid is reintroduced into the shell side of the filter while fluid pressure is still being applied to said lumens.
5. A method of backwashing according to claim 4 wherein feed liquid is reintroduced for a period of between about 1 to about 30 seconds.
- 10 6. A method according to claim 4 wherein said fluid pressure exceeds shell side pressure by about 10kPa to about 800kPa.
7. A method of backwashing according any one of the preceding claims wherein the pressure applied to said lumens prior to said explosive decompression is between about 100 kPa to about 1200 kPa.
- 15 8. A method according to claim 1 wherein during step (b) the filtrate is allowed to drain out of said lumens of its own volition.
9. A method according to any one of the preceding claims wherein the steps of the method are carried out as a continuous process utilizing repetitive cycles of solids retention and backwash.
- 20 10. A concentrator for recovering fine solids from a liquid feed suspension and having an operating cycle including a concentration part of the cycle in which solids present in the feed suspension are concentrated and a backwash part of the cycle in

- 17 -

which supply of feed suspension to the concentrator is interrupted, said concentrator comprising:

- (i) a shell;
- (ii) a plurality of elastic, hollow, microporous, polymer fibres being fixed at  
5 their ends within the shell;
- (iii) means for supplying pressurized feed suspension to the outside of the fibres during said concentration part of the cycle;
- (iv) means for withdrawing filtrate from the fibre lumens during said operating cycle;
- 10 (v) means for terminating the concentration part of the cycle by ceasing supply of feed to said exterior surface of said fibres;
- (vi) means for sealing and opening the shell to atmosphere;
- (vii) means for substantially removing remaining filtrate from said lumens;
- (viii) means for applying a source of fluid under pressure to said lumens before,  
15 at the same time as, or just after opening the shell to atmosphere, to cause explosive decompression through the walls of the fibres whereby said fluid under pressure passes through said walls;
- (ix) means for maintaining the pressure level in said lumens at a predetermined value for a sufficient time following said decompression to cause  
20 substantial portions of solids lodged within and/or on said fibre walls to be dislodged;
- (x) means for washing dislodged contaminant matter away by the application of a flow of liquid over the surface of said fibre walls; and

- 18 -

(xi) means for recommencing the concentration part of the operating cycle by introducing said supply of feed suspension to said exterior surface of said fibres.

11. A concentrator according to claim 10 including means for rewetting the fibres before recommencing concentration.

5 12. A concentrator according to claim 10 or claim 11 wherein the means for substantially removing remaining filtrate includes means for applying fluid pressure to said lumens, said fluid pressure being in the range from about 10 kPa to about 600 kPa.

13. A concentrator according to any one of claims 10 to 12 wherein the means for applying a source of fluid pressure to said lumens before, at the same time as, or just  
10 after opening the shell to atmosphere includes means for pulsing the application of said fluid pressure.

14. A concentrator according to claim 13 wherein the pulses of pressure are between about 0.1 seconds and about 5 seconds in duration.

15. A concentrator according to claim 13 or 14 wherein the means for pulsing the  
15 application of pressure comprises means for opening and sealing the shell at predetermined intervals to allow pressure to build up within said lumens.




FIG. 1





FIG. 2








FIG. 4

4/10





5/10

FIG.6





FIG. 7

7/10



8/10




FIG. 9

9/10





FIG. 10

10/10



## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 95/00587

**A. CLASSIFICATION OF SUBJECT MATTER**Int Cl<sup>6</sup>: B01D 65/02, 61/20, 61/22, 63/02, 65/08, 61/18, 65/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC : Int. Cl<sup>6</sup> B01D 61/18, 61/20, 61/22, 63/02, 65/08, 65/02, 65/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AU : IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DERWENT: ON-LINE, B01D 13/01 and (hollow fibre) period 1984-1989

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	AU,A, 55847/86 (MEMTEC LIMITED) 12 September 1986 See preferred embodiments.	1-15
X	AU,B, 34400/84 (563321) (MEMTEC LIMITED) 23 April 1985 See preferred embodiments.	1-15
Y	AU,A, 77066/87 (MEMTEC LIMITED) 28 January 1988 See preferred embodiments.	1-15



Further documents are listed in the continuation of Box C



See patent family annex

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;"

document member of the same patent family

Date of the actual completion of the international search

1 December 1995

Date of mailing of the international search report

8 DECEMBER 1995

Name and mailing address of the ISA/AU

AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION

PO BOX 200

WODEN ACT 2606

AUSTRALIA Facsimile No.: (06) 285 3929

Authorized officer

GRAEME J BROXAM

Telephone No.: (06) 283 2133

## PCT/INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 95/00587

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO,A, 88/01529 (MEMTEC LIMITED) 10 March 1988 See examples.	1-15
Y	WO,A, 86/05705 (MEMTEC LIMITED) 9 October 1986 See examples.	1-15



**INTERNATIONAL SEARCH REPORT**  
**Information on patent family members**

International Application No.  
**PCT/AU 95/00587**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	55847/86	EP	213157	US	4931186	WO	8605116
		US	5024762	CN	86104888		
AU	34400/84	EP	160014	US	4767539	WO	8501449
AU	77066/87	DK	1312/88	EP	289523	ES	2014516
		US	4935143	WO	880494		
WO	8801529	AU	79637/87	DK	2413/88	EP	380717
		ES	2008734	NO	881925	US	4921610
WO	8605705	AU	56923/86	EP	216876	US	4816160
END OF ANNEX							